

### Indicator lights with colour cap

Rotation-proof  
Option: waterproof IP64 / IP67 / IP68

### Signalleuchten mit Farbkappen


Verdrehsicher  
Option: wasserdicht IP64 / IP67 / IP68

### Voyants lumineux avec capuchon

Anti-rotation  
Option: étanche IP64 / IP67 / IP68

117

119



3D Step-file available on request

**Further specifications and options in section „E-G“ / Weitere Spezifikationen und Optionen in Kapitel „E-G“ / Autres spécifications et options au chapitre „E-G“**

Type / Typ / Type	Body / Körper / Corps		Accessories Zubehör Accessoires	Lens / Linse / Lentille			Light source Lichtquelle Source lum.	Resistor Widerstand Résistance					
	Protection Schutzart Protection	Surface Oberfläche Surface		Style Form Forme	with/mit/ avec Fresnel	Colour Farbe Couleurs		Code	V	mA			
<b>117</b>  Solder lugs Lötösen Contact à souder	4	IP 64	B	1	1	A1	Amber Orange	Y33U 4200 mcd	Yellow Gelb Jaune	0	without ohne sans		
						B1	Blue Blau Bleu			Y30U 1200 mcd	A	5	20
	7	IP 67	S	1	6	6	C1	Clear Klar Clair	Y301 30 mcd		B	12	20
							G1	Green Grün Vert	B71G 6220 mcd		D	24	20
	8	IP 68	9	1	6	6	R1	Red Rot Rouge	B41G 1160 mcd		DB	24	15
							W3	White Weiss Blanc	G41N 17600 mcd G51N 10320 mcd G301 40 mcd		E	28	20
	Type / Typ / Type	Body / Körper / Corps		Accessories Zubehör Accessoires	Lens / Linse / Lentille			R30U 1500 mcd R301 8 mcd			EB	28	14
		Protection Schutzart Protection	Surface Oberfläche Surface		Style Form Forme	with/mit/ avec Fresnel	Colour Farbe Couleurs						
	<b>119</b>  Stranded wire Litze Fil multi-brins Standard 100 mm Other lengths on request Andere Längen auf Anfrage Autres longueurs sur demande	4	IP 64	1	1	1	A1	Amber Orange	W37N 13350 mcd W36N 6900 mcd W32N 3745 mcd	White Weiss Blanche			
							7	IP 67					
8		IP 68	9	6	C1	Clear Klar Clair	RG36 common cathode only series 119 for 24V only 15mA for 28V only 14mA	Red-Green Rot-Grün Rouge-Verte					
					G1	Green Grün Vert							
Type / Typ / Type		Body / Körper / Corps		Accessories Zubehör Accessoires	Lens / Linse / Lentille			R30U 1500 mcd R301 8 mcd			EB	28	14
		Protection Schutzart Protection	Surface Oberfläche Surface		Style Form Forme	with/mit/ avec Fresnel	Colour Farbe Couleurs						
Type / Typ / Type	Body / Körper / Corps		Accessories Zubehör Accessoires	Lens / Linse / Lentille			R30U 1500 mcd R301 8 mcd			EB	28	14	
	Protection Schutzart Protection	Surface Oberfläche Surface		Style Form Forme	with/mit/ avec Fresnel	Colour Farbe Couleurs							
Type / Typ / Type	Body / Körper / Corps		Accessories Zubehör Accessoires	Lens / Linse / Lentille			R30U 1500 mcd R301 8 mcd			EB	28	14	
	Protection Schutzart Protection	Surface Oberfläche Surface		Style Form Forme	with/mit/ avec Fresnel	Colour Farbe Couleurs							

Operating Temperature -30° to +85°C (-40°C to +100°C on request) / Storage Temperature: -40° to +100°C

different LED's of the SLOAN range can be built in

RoHS compliant / \* except surface option 9 (none RoHS)

Specifications are subject to change without notice - Änderungen die dem technischen Fortschritt dienen, sind vorbehalten - Réserve de modifications de toutes les données techniques

