

Indicator lights with reflector

Option: waterproof IP64 / IP67 / IP68

134

135


138

Signalleuchten mit Reflektor

Option: wasserdicht IP64 / IP67 / IP68

Voyants lumineux avec réflecteur

Option: étanche IP64 / IP67 / IP68



3D Step-file available on request

Further specifications and options in section „E-G“ / Weitere Spezifikationen und Optionen in Kapitel „E-G“ / Autres spécifications et options au chapitre „E-G“

Type / Typ / Type	Body / Körper / Corps		Accessories / Zubehör / Accessoires	Light source / Lichtquelle / Source lum.	Resistor / Widerstand / Résistance	
Terminals / Anschlüsse / Raccords	Protection / Schutzart / Protection	Surface / Oberfläche / Surface	nut	LED 3 mm	Code	V mA
134 Solder lugs / Lötösen / Contact à souder	4 IP 64	B Brass, blackened / Messing, geschwärzt / Laiton, noircie	1 0 front mounting	Y33U 4200 mcd Y30U 1200 mcd Y301 30 mcd B71G 6220 mcd B41G 1160 mcd G41N 17600 mcd G51N 10320 mcd G301 40 mcd R33U 4000 mcd R30U 1500 mcd R301 8 mcd W37N 13350 mcd W36N 6900 mcd W32N 3745 mcd RG36 common cathode only series 135 138 for 24V only 15mA for 28V only 14mA	0	without ohne sans
	7 IP 67	S Brass, nickel plated / Messing, vernickelt / Laiton, nickelée			A	5 20
	8 IP 68	9 Brass, olive drab * / Messing, braunoliv * / Laiton, olivebrun *			B	12 20
135 LED terminals / LED-Anschlüsse / Fils des LED	4 IP 64	1 Brass, blackened / Messing, geschwärzt / Laiton, noircie	1 010 Standard (100 mm) Other lengths on request Andere Längen auf Anfrage Autres longueurs sur demande	Y33U 4200 mcd Y30U 1200 mcd Y301 30 mcd B71G 6220 mcd B41G 1160 mcd G41N 17600 mcd G51N 10320 mcd G301 40 mcd R33U 4000 mcd R30U 1500 mcd R301 8 mcd W37N 13350 mcd W36N 6900 mcd W32N 3745 mcd RG36 common cathode only series 135 138 for 24V only 15mA for 28V only 14mA	E	28 20
	7 IP 67	2 Brass, nickel plated / Messing, vernickelt / Laiton, nickelée			DB	24 15
	8 IP 68	9 Brass, olive drab * / Messing, braunoliv * / Laiton, olivebrun *			EB	28 14
138 Stranded wire / Litze / Fil multi-brins	4 IP 64	1 Brass, blackened / Messing, geschwärzt / Laiton, noircie	1 010 Standard (100 mm) Other lengths on request Andere Längen auf Anfrage Autres longueurs sur demande	Y33U 4200 mcd Y30U 1200 mcd Y301 30 mcd B71G 6220 mcd B41G 1160 mcd G41N 17600 mcd G51N 10320 mcd G301 40 mcd R33U 4000 mcd R30U 1500 mcd R301 8 mcd W37N 13350 mcd W36N 6900 mcd W32N 3745 mcd RG36 common cathode only series 135 138 for 24V only 15mA for 28V only 14mA	E	28 20
	7 IP 67	2 Brass, nickel plated / Messing, vernickelt / Laiton, nickelée			DB	24 15
	8 IP 68	9 Brass, olive drab * / Messing, braunoliv * / Laiton, olivebrun *			EB	28 14

Operating Temperature -30° to +85°C (-40°C to +100°C on request) / Storage Temperature: -40° to +100°C

different LED's of the SLOAN range can be built in

RoHS compliant / * except surface option 9 (none RoHS)

Specifications are subject to change without notice - Änderungen die dem technischen Fortschritt dienen, sind vorbehalten - Réserve de modifications de toutes les données techniques

