



3D Step-file available on request



Further specifications and options in section „E-G“ / Weitere Spezifikationen und Optionen in Kapitel „E-G“ / Autres spécifications et options au chapitre „E-G“

| Type / Typ / Type   | Body / Körper / Corps     | Accessories<br>Zubehör<br>Accessoires   |  | Cap / Farbkappe / Cabochon |   |  | Light source<br>Lichtquelle<br>Source lum.  | Resistor<br>Widerstand<br>Résistance   |   |    |
|---|---------------------------|---|--|----------------------------|---|--|---|--|---|----|
|   |                           |   |  | Style<br>Form<br>Forme     | with / mit<br>avec<br>Fresnel           | Colour<br>Farbe<br>Couleurs  |   | Code   | V | mA |
| <b>200</b><br><br>Stranded wire<br>Litze<br>Fil multi-brins<br>Standard 100 mm<br>Other lengths on request<br>Andere Längen auf Anfrage<br>Autres longueurs sur demande | <b>1</b><br>Polycarbonate | <b>1</b><br>Retainer<br>Klemmscheibe<br>Rondelle de serrage<br><br>Rondelle décorative<br>nickel plated<br>vernickelt<br>nickelé<br><br><b>2</b><br>Decorative washer<br>Dekorati-onnscheibe<br>Rondelle décorative<br>black<br>schwarz<br>noir<br> | <b>0</b><br>without<br>ohne<br>sans<br><br><b>1</b><br>Deco-<br>rative<br>washer<br>Dekorati-<br>onnschei-<br>be<br>Rondelle<br>décora-<br>tive<br>nickel<br>plated<br>vernickelt<br>nickelé<br><br><b>2</b><br>Deco-<br>rative<br>washer<br>Dekorati-<br>onnschei-<br>be<br>Rondelle<br>décora-<br>tive<br>black<br>schwarz<br>noir<br> | <b>0</b><br>Standard       | <b>A1</b> Amber<br>Orange<br>Orange<br> | <b>Y54U</b><br>7000 mcd<br><b>Y50U</b><br>3000 mcd<br><b>Y501</b><br>80 mcd<br><br><b>B91G</b><br>9000 mcd<br><b>B21G</b><br>2120 mcd<br><b>B61G</b><br>1160 mcd<br><br><b>G81N</b><br>32500 mcd<br><b>G71N</b><br>5620 mcd<br><b>G501</b><br>80 mcd<br><br><b>R54U</b><br>7000 mcd<br><b>R50U</b><br>3000 mcd<br><b>R521</b><br>80 mcd<br><br><b>W55N</b><br>22000 mcd<br><b>W50N</b><br>2320 mcd<br><br><b>RG5F</b><br>bipolar | Yellow<br>Gelb<br>Jaune<br><br><br>Blue<br>Blau<br>Bleu<br><br><br>Blue<br>Blau<br>Bleu<br><br><br>Green<br>Grün<br>Verte<br><br><br>Green<br>Grün<br>Verte<br><br><br>Red<br>Rot<br>Rouge<br><br><br>White<br>Weiss<br>Blanche<br><br><br>Red-<br>Green<br>Rot-Grün<br>Rouge-<br>Verte<br> | <b>0</b><br>without<br>ohne<br>sans<br><br><b>A</b> 5 20<br><br><b>B</b> 12 20<br><br><b>D</b> 24 20<br><br><b>E</b> 28 20 |   |    |

Operating Temperature -30° to +85°C (-40°C to +100°C on request) / Storage Temperature: -40° to +100°C

different LED's of the SLOAN range can be built in

RoHS compliant

Specifications are subject to change without notice - Änderungen die dem technischen Fortschritt dienen, sind vorbehalten - Réserve de modifications de toutes les données techniques

