



3D Step-file available on request



955YY0B

**Further specifications and options in section „E-G“ / Weitere Spezifikationen und Optionen in Kapitel „E-G“ / Autres spécifications et options au chapitre „E-G“**

Type / Typ / Type	Body / Körper / Corps		Accessories Zubehör Accessoires	Cap / Farbkappe / Cabochon	Light source Lichtquelle Source lum.	Voltage Spannung Tension					
	Surface Oberfläche Surface	Protection Schutzart Protection				Code	V	mA			
<b>955</b>    Screw terminals Schraubanschlüsse Contact à vis   All versions also available as flashing units. Put a "F" for flashing at the end of the part#.  Alle Versionen auch blinkend erhältlich. Bitte ergänzen Sie ein „F“ am Ende der Artikel#.  Version clignotante possible pour tous les modèles. Ajouter la lettre "F" à la référence.	Black Schwarz Noir  Material: ABS Material: ABS Matériel: ABS	IP65	Nut & O-Ring Mutter & O-Ring Ecrou & Joint  	<b>B</b> Blue Blau Bleu	<b>B0</b> 1 LED 3'000mcd 470nm Blue Blau Bleue	<b>B</b> 12V AC/DC	20				
				<b>G</b> Green Grün Vert	<b>G0</b> 1 LED 3'000mcd 525nm Green Grün Verte			<b>D</b> 24V AC/DC	20		
				<b>R</b> Red Rot Rouge	<b>R0</b> 1 LED 800mcd 660nm Red Rot Rouge					<b>J</b> 48V AC/DC	20
				<b>W</b> White Weiss Blanc	<b>W0</b> 1 LED 1'000mcd 6500K White Weiss Blanche						
				<b>Y</b> Yellow Gelb Jaune	<b>Y0</b> 1 LED 800mcd 592nm Yellow Gelb Jaune						

Operating Temperature -25° to +60°C / Storage Temperature: -25° to +60°C

RoHS compliant

Specifications are subject to change without notice – Änderungen die dem technischen Fortschritt dienen, sind vorbehalten – Réserve de modifications de toutes les données techniques

