# Accessories and Replacement Parts (for ø30 XN Series Emergency Stop Switches)

Name & Shape	Material	Part No.	Ordering No.	Package Quantity	Remarks	Switches
Terminal Cover	PPE	XW9Z-VL2M	XW9Z-VL2MPN02	2	Black     Used for screw terminals.     Attached to IP20 protection cover units.	APEM
IP20 Fingersafe Terminal Cover	Polyamide	XW9Z-VL2MF	XW9Z-VL2MFPN02	2	Black Used to change terminal cover to IP20 fingersafe terminal. Only solid wires can be used. Once installed, IP20 terminal cover cannot be removed.	Switches & Pilot Lights  Control Boxes  Emergency Stop Switches  Enabling Switches
Ring Wrench	Brass	XN9Z-T1	XN9Z-T1	1	Used to tighten the locking ring when installing the XN emergency stop switch onto a panel.      90	Safety Products  Explosion Proof  Terminal Blocks  Relays & Sockets  Circuit  Protectors
Ring Wrench	Steel Trivalent chromate plating	TWST-T1	TWST-T1	1	Used to tighten the locking ring when installing the XN emergency stop switch onto a panel.      23.7      77      77	Power Supplies  LED Illumination  Controllers  Operator Interfaces  Sensors  AUTO-ID

- The XN series emergency stop switches are supplied with either terminal cover or IP20 fingersafe terminal cover.
- Padlocks and hasps are not supplied and must be ordered separately.

## Nameplates (for ø30 Emergency Stop Switches)

Description & Shape	Legend	Part No.	Package Quantity	Dimensions (mm)
	(blank)	HNAV-0	4	Polyamide Mounting panel thickness XN4E-□L4: 1.0 to 4.5 mm XN□E-□V4: 1.0 to 3.5 mm
	EMERGENCY STOP	HNAV-27	-	93 <sub>0</sub> 1.5 1.0

Plate color: Yellow (Munsell 2.5Y 8/10 or equivalent), Legend: Black

### Padlock and Hasp


Padlocks and hasps of the following specifications can be used with padlockable emergency stop switches.

#### Padlock Size

a	b	С	d
7 mm maximum	19 mm minimum	39 mm minimum	15 mm minimum (Note)

Note: When the padlock is installed from the side of the bezel, dimension d requires a minimum of 6 mm. When the padlock is installed from the front of the button, dimension d requires a minimum of 15 mm.

### Recommended Hasp



Maker	Part No.
PANDUIT CORP.	PSL-HD3 PSL-1A
Master Lock® Company LLC	420, 421

Use only padlocks or hasps that satisfy the specifications shown on the left. The maximum total weight for padlocks and hasps is 1500g. Make sure that the total weight does not exceed 1500g, otherwise the XN emergency stop switch may be damaged.

Make sure that locking and unlocking of the padlock and hasp do not interfere with other devices.

Padlocks and hasps are available from the following manufacturers.

Manufacturer	URL		
PANDUIT CORP.	http://www.panduit.com/		
Master Lock® Company LLC	http://www.masterlock.com/		

SEMI