


1. SPECIFICATIONS:

HOUSING MATL: ALUMINIUM 6061 T6
 CONNECTION: PVC WIRES 24 AWG
 SWITCHING VOLTAGE: 1 - 24V AC/DC
 SWITCHING CURRENT: 0.200 A
 SWITCH RESISTANCE "ON": < 20 OHMS
 SWITCH RESISTANCE "OFF": > 5 MOHMS
 ACTUATION FORCE: 3-5 N
 MAKE IMPULSE TIME: 125-300 mSEC
 OPERATING AND STORAGE TEMP: -40°C TO $+125^{\circ}\text{C}$

WIRING

RED } 1-24V AC/DC
 RED } 0.2A SWITCH



2. FINISH:

ANODISE THICKNESS: 6-10 μm
 COLOR: NATURAL

	ALUMINIUM 6061 T651	Tolerance ± 0.1				
Itemref	Quantity	Title/Name, designation, material, dimension etc				Article No./Reference
Designed by Moshe	Checked by Armand	Approved /date <i>19/1/03</i>	Filename 10502000_605-600	Drawing_n 605-600	Scale 3:1	Date 19/1/03
	Baran House 8 Omarim St. Omer industrial area 84965 Israel		SMA2AAW1N			
ADVANCED TECHNOLOGIES	Tel. 972-8-6200020 Fax. 972-8-6200021		Cat no. 10502000	Edition 1	Sheet 1/1	