



ORDERING OPTIONS

Example : CD2425W2VH

	C	D	24	25	W	2	V	H
Series	—	—	—	—	—	—	—	—
C	—	—	—	—	—	—	—	—
Cover	—	—	—	—	—	—	—	—
C: Included D: Not Included	—	—	—	—	—	—	—	—
Operating Voltage	—	—	—	—	—	—	—	—
24: 24-280 VAC 48: 48-600 VAC	—	—	—	—	—	—	—	—
Rated Load Current	—	—	—	—	—	—	—	—
25: 25 Amps 50: 50 Amps	—	—	—	—	—	—	—	—
Control Voltage	—	—	—	—	—	—	—	—
W: 4-32 VDC	—	—	—	—	—	—	—	—
Input Connector	—	—	—	—	—	—	—	—
2: Key Locking Connector 3: 4 Pin Connector accepting Screw Terminals 4: 4 Pin Spring Terminal	—	—	—	—	—	—	—	—
Output Terminal Orientation	—	—	—	—	—	—	—	—
U: A channel top, B channel bottom V: A channel on left, B channel on right	—	—	—	—	—	—	—	—
Thermal Pad	—	—	—	—	—	—	—	—
Blank: Not Included H: Included	—	—	—	—	—	—	—	—

— Required for valid part number

□ For options only and not required for valid part number